



Submittal Data Information

“MPT” Option C Grooved Vertical Multi-Purpose Tanks With 2 Internal Pall Ring Baskets

401-210

SUPERSEDES: June 16, 2016

EFFECTIVE: September 3, 2019

Job: _____


ITEM	LOCATION	MODEL	QUANTITY	GALLONS
------	----------	-------	----------	---------

SPECIFICATIONS

- Designed and constructed per ASME Code Section VIII, Division 1.
- Construction: Carbon Steel with exterior red oxide primer finish
- Standard Design Pressure and Temperature: 125 psi @ 240°F
- Flanged inlet and outlet System Connections (standard sizes shown)
- Registered with the National Board of Pressure Vessel Manufacturers
- Integral Air Vent (Suitable for water, max. 50% glycol)
- Factory installed 2" Blow Down Valve
- Brass Flushing Cock
- 304 stainless steel coalescence pall rings
- U-1A Data Report
- (1) 2" NPT Inspection Opening – MPT0050 thru MPT0350
- (2) 4"X6" Inspection Handholes – MPT0400 thru MPT1050
- (1) 3/4" Temperature/ Pressure port on shell

OPTIONS (Consult Factory)

- Optional materials of construction
- Higher design pressures and temperatures
- Optional System Connection sizes available
- Thermal insulation
 - ☐ None
 - ☐ Chilled Water 1/2" Armaflex
 - ☐ Heating Water 1" Silicon Blanket
 - ☐ Other _____
- Optional Connection Types
 - ☐ "T" Female NPT Threaded 2" & 2 1/2" only. Available only on sizes, MPT0050 thru MPT0350
- 3/4" NPT Temperature/ Pressure Ports
 - ☐ (5) 3/4" Temperature/ Pressure ports: One port on shell and on each nozzle
- ☐ Optional Anchor Clips
- ☐ 150 PSI Working Pressure



***Complete Model Number as shown below:**
MPT0050G04-125N1CN

SIZES & DIMENSIONS

All dimensions shown are subject to change and should not be used for pre-piping. Contact your local Taco representative should certified dimensional drawings be required.

NOZZLE SIZES OFFERED
Circle desired size below.



MODEL NUMBER	TANK VOLUME	A DIAMETER	B	C**	D	E DIAMETER	F	G	APPROX. WEIGHT
	GAL.	INCH	INCH	INCH	INCH	INCH	INCH	SIZE	LBS.
MPT0050G_-125N1CN	50	20	43	25	11 1/2	18	12 7/8	2, 3, 4	310
MPT0075G_-125N1CN	75	24	46	29	12 5/8	20	12 7/8	2, 3, 4	360
MPT0100G_-125N1CN	100	24	61	29	12 5/8	20	12 7/8	2, 3, 4	400
MPT0125G_-125N1CN	125	24	76	29	12 5/8	20	12 7/8	2, 3, 4	450
MPT0150G_-125N1CN	150	30	60	35	14 1/4	24	13 1/2	2, 3, 4	640
MPT0180G_-125N1CN	180	30	71	35	14 1/4	24	13 1/2	2, 3, 4	720
MPT0200G_-125N1CN	200	30	78	35	14 1/4	24	13 1/2	2, 3, 4	760
MPT0250G_-125N1CN	250	36	69	41	16 3/4	30	13 1/2	3, 4, 6	890
MPT0300G_-125N1CN	300	36	82	41	16 3/4	30	13 1/2	3, 4, 6	1000
MPT0350G_-125N1CN	350	36	94	41	16 3/4	30	13 1/2	3, 4, 6	1090
MPT0400G_-125N1CN	400	48	65	53	19 5/8	44	12 7/8	4, 6, 8	1310
MPT0450G_-125N1CN	450	48	72	53	19 5/8	44	12 7/8	4, 6, 8	1380
MPT0500G_-125N1CN	500	48	79	53	19 5/8	44	12 7/8	4, 6, 8	1460
MPT0700G_-125N1CN	700	48	100	53	19 5/8	44	12 7/8	4, 6, 8	1600
MPT0850G_-125N1CN	850	54	99	59	23 1/2	50	13 1/8	4, 6, 8	2190
MPT1050G_-125N1CN	1050	60	99	65	25 3/4	54	14	6, 8, 10	2500

Nozzle Ports are shown for placement and clarity only.

** Add 1" to "C" dimension when specifying 10" nozzles

** Add 4" to "C" dimension when specifying 1.5" or thicker insulations

Taco Comfort Solutions A Taco Family Company

Taco, Inc., 1160 Cranston Street, Cranston, RI 02920 | Tel: (401) 942-8000 | FAX: (401) 942-2360

Taco (Canada), Ltd., 8450 Lawson Road, Suite #3, Milton, Ontario L9T 0J8 | Tel: (905) 564-9422 | FAX: (905) 564-9436

Visit our web site: www.TacoComfort.com | Printed in USA | ©2019 Taco, Inc.

