

Submittal Data Information

TA Series Pumps

301-662

EFFECTIVE: April 11, 2014

SUPERSEDES: January 17, 2014



3500 RPM MODEL 1024

JOB _____ ENGINEER _____

CONTRACTOR _____ REP. _____

ITEM NO.	MODEL NO.	IMPELLER DIA.	G.P.M.	HEAD/FT.	H.P.	ELEC. CHAR.
----------	-----------	---------------	--------	----------	------	-------------

WEIGHT _____ PUMP/MOTOR _____



Clockwise Rotation
viewed from the Coupling End

Counterclockwise Rotation
viewed from the Coupling End

SPECIFY ROTATION:

- ☐ Clockwise
☐ Counterclockwise

MAXIMUM ASSEMBLY WEIGHT

Motor Frame	Weight Lbs (Kg)
364TS - 365TS	1402 (636)
404TS - 405TS	1733 (786)
444TS - 445TS	2121 (962)

DIMENSIONS

Motor dimensions are approximate and vary by manufacturer and motor type.

Model No. Flange Size	HP 3500 RPM	Motor Frame*	A DISCHARGE		B SUCTION		C	D	E	F	G	H	J	K	L	M	N	P	
			ANSI Class 125	ANSI Class 250	ANSI Class 125	ANSI Class 250													
1024 6 x 4 (152 x 102)	60	364TS	0.94 (24)	1.25 (32)	1.00 (25)	1.44 (37)	21.17 (538)	19.92 (506)	9.81 (249)	12.19 (310)	11.81 (300)	6.69 (170)	27.75 (705)	9.5 (241)	27.00 (686)	17.57 (446)	54.0 (1372)	33.4 (848)	
	75	365TS					27.17 (690)	25.92 (658)									64.0 (1626)	38.3 (973)	
	100	404TS																	
		405TS																	
	125	444TS																	44.6 (1133)
	150	445TS																	

English dimensions are in inches. Metric dimensions are in millimeters. Metric data is presented in ().

Dimensions are subject to change without notice. Do not use for construction purposes unless certified.

* Frame size reflects TEFC enclosure. ODP enclosure is typically one size smaller. Please consult Taco or motor manufacturer for specific frame size for ODP and other non-TEFC enclosures.

MATERIALS OF CONSTRUCTION

Item	Standard	Optional
Casing	Cast Iron ASTM A48 Class 30A	N/A
Impeller	Bronze ASTM B584-836	N/A
Wear Ring	Bronze ASTM B584-836	N/A
Shaft	Carbon Steel AISI 1045	Stainless Steel AISI 420
Insert	Cast Iron ASTM A48 Class 30A	N/A
Shaft Sleeve	Bronze ASTM B584-836	Stainless Steel AISI 420

N/A - Not Available

OPERATING SPECIFICATIONS

	Standard	Optional
Flange	ANSI Class 125	ANSI Class 250
Pressure	175 PSIG* (1210 KPA)	300 PSIG** (2070 KPA)
Temperature	250°F (120°C)	250°F (120°C)


Motors: All NEMA Standard (T Frame)

* In accordance with ANSI Standard B16.1 Class 125

** In accordance with ANSI Standard B16.1 Class 250 Dim.

FEATURES

	Standard	Optional
Wear Rings	Case Wear Rings	N/A
Seal Flushing	Recirculation Line	Filter & Abrasive Separators
Motors	All Standard NEMA Motors	
Base	Drip Type Base	
Additional Options	Packed Stuffing Box Two Rotation Options Balanced Mechanical Seals	



Comments: _____

Taco® Comfort Solutions™ A Taco Group Company

Taco, Inc., 1160 Cranston Street, Cranston, RI 02920 | Tel: (401) 942-8000 | FAX: (401) 942-2360

Taco (Canada), Ltd., 8450 Lawson Road, Suite #3, Milton, Ontario L9T 0J8 | Tel: (905) 564-9422 | FAX: (905) 564-9436

Visit our web site: www.TacoComfort.com | Printed in USA | ©2015 Taco, Inc.

