

**HPU2 Water Source Heat Pump Controller**  
***Self-Contained Interoperable Controller Model UCP-1***

SUPERSEDES: April 12, 2011

EFFECTIVE: June 11, 2012

Job: \_\_\_\_\_ Engineer: \_\_\_\_\_  
Contractor: \_\_\_\_\_ Rep: \_\_\_\_\_  
Date: \_\_\_\_\_ Tag/Item #: \_\_\_\_\_

## HPU2

The HPU2 heat pump controller is a stand-alone microprocessor-based controller for liquid source heat pump units. The application includes liquid source heat pump units with two-stage compressor, reversing valve and fan.

### Overview

A digital input is provided to monitor equipment status. A two-wire serial interface is provided for the thermostat. The HPU2 incorporates digital outputs in the form of triacs for fan start/stop, two compressor stages, and a reversing valve.

The controller is based on LONWORKS<sup>®</sup> networking technology. The controller can be networked to a higher-level control system for monitoring and control applications.

### Features

- Two stage compressor heating/cooling control
- Reversing valve control
- Local backup schedule
- Individual temperature setpoints for occupied/unoccupied heat and cool
- LONWORKS interface to building automation systems
- Equipment status input for additional safety interlocks
- Thermostat with space temperature, setpoint adjust, fan override, occupancy override
- Fan control energized on call for heating or cooling
- Automatic heat/cool changeover
- Global unit enable for main plant synchronization
- Remote sensor capabilities
- Automatic configuration with the LCI
- Real Time Clock
- Alarm/Event reporting

## SPECIFICATIONS

### Electrical

#### Inputs

- Cabling: twisted shielded pair, 18 AWG recommended—500 feet max. (152 meters)

- Resolution: 10 bit

#### Stat

- iWorx® TS300 Series

#### Equipment Status

- Dry Contact
- Normally Open
- 5 Volts DC Max

#### Space Temp (optional)

- Precon Type II or Type III 10K thermistor

### Outputs

#### Stage 1, Stage 2, Reversing Valve, and Fan

- 24 Volts AC
- 1A @ 50C, 0.5A @ 60C, limited by the Class 2 supply rating

### Power

#### Power Requirements

- 24VAC (20VAC to 28VAC), requires an external Class 2 supply

#### Power Consumption

- 7.2W with no external loads, maximum limited by the Class 2 supply rating

### Recommended Sensor Wire

Cable Type	Pairs	Details	Taco Catalog No.
18AWG	1	Stranded Twisted Shielded Pair, Plenum	WIR-018

### FTT-10A Network

- Speed: 78KBPS
- Cabling: Maximum node-to-node distance: 1312 feet (400 meters)
- Maximum total distance: 1640 feet (500 meters)

Cable Type	Pairs	Details	Taco Catalog No.
Level 4 22AWG (0.65mm)	1	Unshielded, Plenum, U.L. Type CMP	WIR-022

For detailed specifications, refer to the *FTT-10A Free-Topology Transceiver User's Guide* published by Echelon Corporation ([www.echelon.com/support/documentation/manuals/transceivers](http://www.echelon.com/support/documentation/manuals/transceivers)).

## Mechanical

### Housing

- Dimensions: 5.55" (141mm) high, 6.54" (166 mm) wide, 1.75" deep (44 mm)
- ABS

### Weight

- Controller Weight: 0.70 pounds (0.32 kilograms)
- Shipping Weight: 1.0 pounds (0.46 kilograms)

### **Electronics**

- Processor: 3150 Neuron 10 MHz
- Flash: 48 Kilobytes
- SRAM: 8 Kilobytes
- Termination: 0.197" (5.0 mm) Pluggable Terminal Blocks, 14-22 AWG

### **Environmental**

- Temperature: 32 °F to 140 °F (0 °C to 60 °C)
- Humidity: 0 to 90%, non-condensing

### **Agency Listings**

- UL Listed for US and Canada, Energy Management Equipment PAZX and PAZX7.

### **Agency Compliances**

- FCC Part 15 Class A

## **CONTROLS MADE EASY®**

**Taco Electronic Solutions, Inc.**, 1160 Cranston Street, Cranston, RI 02920  
Telephone: (401) 942-8000 FAX: (401) 942-2360.

**Taco (Canada), Ltd.**, 8450 Lawson Road, Unit #3, Milton, Ontario L9T 0J8.  
Telephone: 905/564-9422. FAX: 905/564-9436.

**Taco Electronic Solutions, Inc. is a subsidiary of Taco, Inc.**

**Visit our web site at:** <http://www.taco-hvac.com>